


# Promo Scrape impressions

→ LOGO MATS • OUTDOOR & INDOOR



## → WHY CHOOSE THIS MAT?

**Promoscraper mats feature your custom logo or artwork on nylon fibers.**

- Unique blend of nylon fibres provides **superior scraping** action against dirt and debris
- High-quality dyes offer brilliant **colour fastness** and **image durability**
- Strong rubber backing provides maximum durability in **high traffic** applications
- In-house designers for a **quick** turnaround time
- **Drainage holes** available for sizes up to 130 x 200 cm
- Fully launderable


## → SPECIFICATIONS

<b>SKU</b>	5785 (Outdoor) ; 5786 (Indoor)
<b>Yarn</b>	100% nylon (4630 Dtex)/(BCF/Monofilament)
• Construction	1/8th gauge cut pile
• Colours	See color range, No Pantone (PMS)
• Pile weight	715 gms/m <sup>2</sup>
• Pile height	7 mm
• Stitch rate	6 spi
• Primary backing	Non woven spun bonded polyester
<b>Backing</b>	UVR Nitrile
• Pattern	Claw
• Drainage holes	Indoor: n.a. Outdoor: Ø 7mm
• Thickness	2.5 mm
• Mat weight	3.9 kg/m <sup>2</sup>
<b>Properties</b>	
• Water retention	3.160 kgms/m <sup>2</sup>
• Total weight	3,9 kgms/m <sup>2</sup>
• Flammability	Dfl-s1
<b>Border</b>	
• Width	20 mm
• Thickness	2,5 mm

## → SPECIAL SIZES

**Indoor** – Max. width: 200 cm, Max. length upon request

**Outdoor** – Max. width: 130 cm, Max. length upon request



## → COLORS

A1	B8	D5
A2	B9	D6
A3	B10	D7
A4	C1	D8
A5	C2	D9
A6	C3	D10
A7	C4	E1
A8	C5	E2
A9	C6	E3
A10	C7	E4
B1	C8	E5
B2	C9	E6
B3	C10	E7
B4	D1	E8
B5	D2	E9
B6	D3	E10
B7	D4	

## → STANDARD SIZES

60x85	85x300*	115x240*	150x250*
75x85	115x180	115x250*	150x300*
85x115	115x200	115x300*	200x200*
85x150	115x300*	150x200*	200x300*
85x240*	115x200*	150x240*	

\* Indoor Only

**Size Tolerance:** +/- 2% -

**Weight Tolerance:** +/- 5%

# → CLEANING INSTRUCTIONS



1. Pre-wash	2-3 mins	Medium	Cold
2. Drain	1 min		
3. Pre-wash <sup>1</sup>	2-3 mins	Medium	Cold
4. Drain	1 min		
5. Main wash <sup>2</sup>	5-8 mins	High	40-50 °C
6. Drain	1 min		
7. Rinse 1	2 mins	High	Cold
8. Drain	1 min		
9. Rinse 2	2 mins	High	Cold
10. Drain	1 min		
11. Extract <sup>3</sup>	8-10 mins		

## Notes

**1.** Optional

**2.** A neutral (pH 7) nonionic detergent is recommended for printed mats. The use of Alkaline built products is not recommended.

**3.** When extracting perforated mats a single high speed extraction is recommended (maximum G Force 600G). If non perforated mats or mixed loads of perforated mats are being extracted then a split extraction cycle, as below, is recommended to achieve optimum water extraction.

**4.** Due to the abrasive nature of the pile, the logo scraper mat may attract lint if washed with other mat types, it is therefore recommended that logo scraper mats are not mixed with other mat types during washing. If however mixed products are washed together, to minimise the linting, the mats should be tumble dried.

## Split Extraction Cycle and Drying



1. Extract	2 mins	Low speed
2. Drain	1 min	Wash Speed
3. Extract	5 mins	High speed



1. Dry	10-15 mins	Max. 80°C
2. Cool down	5 mins	

## Notes

Lay mats flat following removal from dryer. Allow mats to cool before rolling. Roll mats pile out for delivery. Never store printed mats folded or layed pile to pile when damp, to avoid colour transfer.